Sources Microphone console



- Touch interface
- From 16 to 64 programmable keys
- Audio Bus architecture
- Easy and quick installation
- Inconspicuous and multipurpose

The **GXT-4000-XX** is a touchscreen call microphone console: from 16 to 64 programmable keys. Carefully studied by our engineers, it works on a bus architecture, ensuring RS485 communication, power supply distribution and share of a same audio channel.

Connection of consoles is therefore made from one console to the other one, without having to go through the central element. Provided with an electret microphone, a touchscreen, 1 memory card holder, 1 monitoring loudspeaker, 1 limp button with cap and 1 stylus, this console meets all your needs in Public Address.

Either put on a table or flush-mounted, this console can be used in several application types.

30/01/208 10:58	8 21 Entr	ée Nord		兴
17 Parking Niv -1	21 Entrée Hord	25	29	С
18	22	26	30	Ξ¤
19	23	27	31	<u> </u>
20	24	28	32	
MENU				

Features

Message reader		SD cards
Series connection	Bus	RS 485
Power supply	24 VDC	Cons. : 110 mA max
Dimensions		287 x 237 x 73 mm
Color	Grey console	Black base
Material		Metal
Weight		2,5Kg

Applications

Speech.....

Checkpoints

Meeting points

Information

Offices




GXT-4000-XX

Sources

Microphone console


Top view

- 1 Electret microphone
- 2 Touchscreen
- 3 Memory card holder
- 4 « limp » button with cap
- 5 Monitoring loudspeaker
- 6 Stylus holder



Bottom view

- **1** Grommet for button with cap connector
- 2 Ground lug
- RJ 45 In / Out plugs



Side view

- 1 24V power supply jack plug
- 2 Sub D9 (RS 232) plug for soft downloading



Bus connection principle



Central equipment Type CC3816

Bus

CAT5 – type cable

RJ45-RJ45 right 8 conductors



- 1 bus audio pair
- 1 RS485 pair
- 1 free pair
- 1 x 24Vdc power supply pair

